

Winkhaus OBV Safety Catch Restrictors

Restrictors for PVCu and Timber Windows



in
Windows

Winkhaus UK Ltd

2950 Kettering Parkway, Kettering,
Northants NN15 6XZ
Tel: +44 (0)1536 316091
Fax: +44 (0)1536 419091

www.winkhaus.co.uk
email: enquiries@winkhaus.co.uk

Winkhaus OBV Safety Catch Restrictor

Restrictors for PVCu and Timber Windows

OBV Safety Catch Features

- 5 screws- 3 easy steps
- Restricts opening to 50mm - 100mm
- Push button release
- Non-locking and Grub screw locking options available
- Automatically restricts window opening
- Perfect for retrofitting to existing windows
- Available in White or brown

OBV Safety Catch Restrictor

The Winkhaus OBV Safety Catch and OBVA (grub screw locking) are a family of window restrictors, which are designed to help prevent small children opening windows fully and falling out.

An extensive range of angle packers is available to allow the OBV Safety Catch Restrictor to be fitted to PVCu windows.



Key features:

The robust design incorporates the following features:

- The OBV automatically prevents the opening of a window greater than 50mm - 100mm (depending on the positioning on the window).
- The OBV locking bar can be released for full opening of the sash by keeping the push button depressed.
- The OBV will automatically re-engage when the window is closed.
- Surface mounted vertically or horizontally on both outward opening and inward opening windows, it can be retrofitted to existing windows as an additional security and safety device.
- 3mm adjustment of steel hook possible for correct operation.
- Easily fitted using 5 screws. The steel hook is fixed with three screws (for PVCu windows fixing into reinforcement is recommended). Drill jigs available for both site fixing or factory fixing.
- An extensive range of packers and mounting blocks available
- 1mm shims available for optimum positioning of steel hook.
- Purpose designed to provide high levels of child safety and increased security for both new and existing windows, together with a lockable 50mm vent position.
- Can be fitted by eye utilising aligning mark on body of Safety Catch. The line can be transferred using a pencil to indicate the position for the hook base plate.
- The OBV is available in white and brown as standard.

